ACCURACY (continued)

Physical input range of the sensors

ТҮРЕ	MEASUREMENT ACCURACY ^[1]
(10 to 400) Ω	Cu10, Cu50, Cu100, polynomial RTD, Pt50, Pt100, Ni100, Ni120
(10 to 2000) Ω	Pt200, Pt500, Pt1000, Ni1000
(-20 to 100) mV	Thermocouple type: C, D, E, J, K, L, N, U
(-5 to 30) mV	Thermocouple type: B, R, S, T

[1] % is related to the adjusted measurement range (the value to be applied is the greater)

General

Repeatability	0.0015% of the physical input range (15 Bit) Resolution A/D conversion: 18 Bit
Load influence	\leq ± 0.005%/V deviation from 24 V, related to the full-scale value
Long term stability	≤ 0.1 °C [0.18 °F] / year or ≤ 0.05%/year Date under reference conditions. % relates to the set span. The larger value applies.

Temperature Drift

	Effect on the accuracy when ambient temperature changes by 1 °C [1.8 °F]		
	Input (10 to 400) Ω	0.001% of measured value, minimum 1 m $\boldsymbol{\Omega}$	
Total temperature drift =	Input (10 to 2000) Ω	0.001% of measured value, minimum 10 m $\boldsymbol{\Omega}$	
input temperature drift + output temperature drift	Input (-20 to 100) mV	typ. 0.002% of measured value, minimum 0.2 μV	
	Input (5 to 30) mV	typ. 0.001% of measured value, minimum 0.2 μV	
	Output (4 to 20) mA	typ. 0.001% of span	

INSTALLATION CONDITIONS

Ambient Conditions

Ambient temperature	Without display: (-40 to 85) °C [-40 to 185] °F With display: (-40 to 80) °C [-40 to 176] °F
	NOTE: The display can react slowly for temperature < -20 °C [< -4 °F]
Storage temperature	Without display: (-50 to 100) °C [-58 to 212] °F With display: (-50 to 80) °C [-58 to 176] °F
Allowable Altitude	6560 ft. above sea level
Climatic class	As per EN 60 654-1, Class C
Moisture condensation	Allowable
Shock and vibration protection	3 g / (2 to 150) Hz according to IEC 60 068-2-6
EMC immunity	Interference immunity and interference emission as per EN 61 326-1 (IEC 1326) (0.08 to 2) GHz 10 V/m; (1.4 to 2) GHz 30 V/m to EN 61 000-4-3
Protection	IP67, NEMA 4X, Class 1, Division 1, Group A, B, C; Class II Division I, Groups E, F, G and Class III, Division I (when specified)

HART® is a registered trademark of HART Communication Foundation



INTERFACE



Operating Elements

No operating elements are present directly on the display. The device parameters of the field transmitter are configured using the handheld communicator or a PC with HART® Modem and operating software TransComm Light.

Remote Operation

Interface	HART [®] communication via transmitter power supply
Configurable device parameters	Sensor type and connection type, engineering units (°C/°F), measurement ranges, internal/external cold junction compensation of wire resistance with 2-wire connection, failure mode, output signal (4 to 20) mA (20 to 4) mA, digital filter (damping), offset, TAG+descriptor (8+16 characters), output simulation, customized linearization, recording of min./max process value, analog output: Option: customized linearization

STANDARDS

Approvals	
CE marked	Unit complies with the legal requirements set forth by the EU regulations.
APPROVED SD.	Intrinsically safe and non-incendive or explosion proof for hazardous locations Class I, Division 1 and 2, Groups A, B, C and D
Other standards and guidelines	 IEC 60 529: Degrees of protection through housing (IP code) IEC 61 010: Protection measures for electrical equipment for measurement, control, regulation and laboratory procedures IEC 1326: Electromagnetic compatibility (EMC requirements)

HART® is a registered trademark of HART Communication Foundation



MECHANICAL CONSTRUCTION

Dimensions	Display rotatable in 90° increments
Weight	approximately 1.6 kg [3.53 lb]
Materials	Housing: die-cast aluminum with powder coating
Terminals	Cables / wires up to max. 2.5 mm ² (AWG 12)

Terminal Connections



Optional Mounting Bracket

Part Number: 17614 Stainless Steel Wall/Tube Kit - Figure A or B.

Part Number: 17615 Stainless Steel Pipe Mounting Kit - Figure C.

Designed for use on pipes with a diameter of 2".



HART® is a registered trademark of HART Communication Foundation

